



**KAPCI**  
COATINGS

## Technical Data Sheet

Issue June 2021

for professional use only

# Kapci 450 NC Putty

## Product description

Kapci 450 is an extra rapid 1K putty based on a nitrocellulose resins blend. It is used for fine and smooth leveling of minor irregularities, scratches, and pores.

## Substrates

Kapci 450 NC putty should be applied in thin layers over 2K PE putties, primers/fillers, glass fiber reinforced plastic (GRP), and old paints previously sanded properly.

## Application



### Application:

Apply by knife. Apply in 1-2 thin coats.

When necessary, repeat the operation more times. Allow drying for 5-10 minutes between coats.



### Drying time at 20°C:

Dry to sand: approximately 20 min



### Machine or manual dry sanding:

The following grades of sanding papers are recommended:  
P400 or P500



### Manual wet sanding:

The following grades of sanding papers are recommended:  
P800 or P1000

## Recoatable

Kapci 450 is recoatable after sanding.

## Other tips

After applying Kapci 450 NC putty, clean used tools with NC thinner.

## Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment

**IMPORTANT NOTE:** These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.